

AMENDMENTS

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

CLAIMS:

1. (Cancelled)

2. (Currently Amended)

A modular refrigeration unit according to claim 1 in which for use in a refrigeration cabinet, the refrigeration cabinet including a condenser chamber having at least one insulated wall portion with at least one mating surface thereon and an insulated main chamber, said at least one mating surface defining an opening between the condenser chamber and the main chamber, the modular refrigeration unit comprising:

a condenser assembly comprising:

a condenser, for condensing a refrigerant therein;

a condenser fan, for directing a flow of air through the condenser, to remove heat from the condenser;

a condenser fan motor to drive the condenser fan;

a compressor for compressing the refrigerant;

an evaporator assembly comprising:

an evaporator, for evaporating the refrigerant therein;

an evaporator tray positioned beneath the evaporator for collecting moisture condensed thereon;

an evaporator fan for directing a flow of air through the evaporator;

an evaporator fan motor to drive the evaporator fan;

the condenser assembly including a condenser tray for collecting and dissipating moisture condensed on the evaporator and directed to the condenser tray;

a bulkhead assembly positioned between the condenser assembly and the evaporator assembly, the bulkhead assembly ~~includes~~including a bulkhead ~~portion-periphery;~~ and

a gasket assembly coupled to one of said bulkhead ~~positioned around a periphery and said at least one mating surface;~~ ~~of and~~

the bulkhead body portion, assembly being receivable in the opening upon movement of the modular refrigeration unit in a direction substantially transverse to the bulkhead assembly for engaging the gasket assembly being adapted for engaging with the other of said bulkhead periphery and said at least one mating surface to form a substantially air-tight seal between the condenser chamber from and the main chamber.

3. (Currently Amended)

A modular refrigeration unit according to claim 2 in which the gasket assembly ~~includes~~comprises a gasket portion and a thermal breaker portion, the thermal breaker portion being mounted on the periphery of the bulkhead body portion.

4. (Original)

A modular refrigeration unit according to claim 2 in which the gasket portion comprises at least three flexible vanes protruding outwardly from the periphery and adapted to engage with said at least one mating surface to form a substantially air-tight seal.

5. (Currently Amended)

A modular refrigeration unit according to claim 4 in which the vanes comprise ~~rubber~~ an elastomer.

6. (Original)

A modular refrigeration unit according to claim 1 in which the condenser fan is positioned for creating a flow of air into the condenser chamber in a predetermined direction towards the condenser and the compressor, to cool the condenser and the compressor.

7. (Original)

A modular refrigeration unit according to claim 6 in which the predetermined direction of said air flow directed towards the condenser and the compressor is substantially parallel to the bulkhead body portion.

8. (Currently Amended)

A refrigerator ~~including~~comprising:

a refrigeration cabinet ~~having~~comprising insulated outer walls and at least one access door for accessing an insulated main chamber of the cabinet;

the refrigeration cabinet ~~including~~comprising a condenser chamber extending inwardly from an aperture in an outer wall of the cabinet, the condenser chamber being at least partially defined by at least one insulated interior wall portion with at least one mating surface thereon, said at least one mating surface being positioned distal to the aperture, said at least one mating surface defining an opening between the condenser chamber and the main chamber;

a modular refrigeration unit installed in the cabinet, the modular refrigeration unit ~~having~~comprising:

a condenser assembly, ~~including~~ comprising:

a condenser for condensing a refrigerant therein;

a condenser fan, for directing a flow of air through the condenser, to remove heat from the condenser;

a condenser fan motor to drive the condenser fan;

a compressor for compressing the refrigerant;

an evaporator assembly, ~~including~~ comprising:

an evaporator, for evaporating the refrigerant therein;
 an evaporator tray positioned beneath the evaporator, for
 collecting condensed moisture;
 an evaporator fan for directing a flow of air through the
 evaporator;
 an evaporator fan motor to drive the evaporator fan;
 the condenser assembly ~~including~~comprising a condenser tray for
 collecting and dissipating moisture condensed on the evaporator and
 directed to the condenser tray;
 a bulkhead assembly positioned between the condenser assembly and the
 evaporator assembly; ~~and, the bulkhead assembly including a periphery,~~
~~and a gasket assembly positioned around the periphery;~~
the bulkhead assembly being receivable in the opening upon movement of
the modular refrigeration unit in a direction substantially transverse to the
bulkhead assembly; and
the gasket assembly being engageable with said at least one mating
surface to form a substantially air-tight seal, whereby between the
~~condenser assembly is substantially insulated from~~chamber and the main
 chamber when the bulkhead assembly is positioned in the opening.

9. (Currently Amended)

A refrigerator according to claim 8 additionally ~~including~~comprising:

an evaporator shield assembly positioned in the main chamber for
 channelling a circulatory air flow in the main chamber through the
 evaporator;
 a plenum positioned adjacent to the evaporator, for guiding the circulatory
 air flow along a predetermined circulatory air flow path; and
 a partition positioned substantially vertically in the main chamber for
 directing at least a portion of the circulatory air flow toward the
 evaporator.

10. (Currently Amended)
A refrigerator according to claim 9 in which the plenum and the partition partially define an interior chamber portion of the main chamber, the plenum and the partition ~~including~~comprising a plurality of openings formed to direct a predetermined volume of air following the circulatory air flow path into the interior chamber portion.
11. (Currently Amended)
A refrigerator according to claim 8 in which ~~the~~said at least one insulated interior wall portion extends from the aperture in the outer wall to said at least one mating surface to form a condenser chamber floor on which the modular refrigeration unit is positioned when the bulkhead assembly is positioned in the opening.
12. (Currently Amended)
A refrigerator according to claim 8 in which ~~the~~said at least one insulated interior wall portion extends from the aperture in the outer wall to said at least one mating surface to form a condenser chamber ceiling disposed above the modular refrigeration unit when the bulkhead assembly is positioned in the opening.
13. (Currently Amended)
A refrigerator according to claim 8 in which said at least one mating surface ~~is~~comprises a thermal breaker.
14. (Original)
A refrigerator according to claim 13 in which the thermal breaker forms a peripheral ledge positioned to engage the bulkhead assembly to form an air-tight seal.
15. (Cancelled)

16. (Currently Amended)

A refrigerator according to claim 15 in which the gasket assembly ~~includes~~comprises a gasket portion and a thermal breaker portion attached to each other.

17. (Currently Amended)

A refrigerator according to claim 16 in which the bulkhead assembly includes a bulkhead body portion and the thermal breaker portion is mounted on the bulkhead body portion.

18. (Currently Amended)

A refrigerator according to claim 16 in which the bulkhead assembly includes a bulkhead body portion and the thermal breaker portion is embedded in the bulkhead body portion.

19. (Original)

A refrigerator according to claim 11 in which the aperture in the outer wall of the refrigeration cabinet extends above the condenser assembly, such that the flow of air directed through the condenser chamber flows towards the condenser and the compressor in a predetermined path.

20. (Currently Amended)

A refrigerator according to claim 19 in which the refrigeration cabinet ~~includes~~comprises a grille positioned above the condenser chamber, the grille ~~including~~comprising a first set of louvers positioned to guide the flow of air into the condenser chamber from the ambient atmosphere in the predetermined path, ~~and~~a second set of louvers positioned to guide the flow of air out of the condenser chamber in the predetermined path and to substantially prevent immediate recirculation of air into the condenser chamber.

21. (Currently Amended)

A refrigerator according to claim 8 in which the refrigeration cabinet ~~includes~~comprises a secondary access door positioned in a substantially planar second outer wall of the cabinet for accessing the main chamber, the secondary access door being movable between an open position and a closed position, the second outer wall of the cabinet ~~including~~comprising an opening for receiving the secondary access door such that, when the secondary access door is in the closed position, an exterior surface of the secondary access door is substantially flush with an external surface of the second outer wall.

22. (Currently Amended)

A refrigerator according to claim 21 in which the second outer wall ~~includes~~comprises a ridge projecting into the opening, the ridge being spaced back from the external surface of the second outer wall to permit the exterior surface of the secondary access door to be substantially flush with the external surface of the second outer wall when the secondary access door is in the closed position.

23. (Original)

A refrigerator according to claim 22 in which the second outer wall has a predetermined thickness of insulation therein and the secondary access door has a thickness of insulation substantially equivalent thereto, for insulating the main chamber from the ambient atmosphere.

24. (Currently Amended)

A gasket assembly for use with a mating surface including a first thermal breaker portion in a refrigeration cabinet, the gasket assembly ~~including~~comprising:

- a second thermal breaker portion adapted for attachment to a bulkhead body portion around a ~~peripheral edge~~periphery thereof; and
- a flexible gasket portion attached to the second thermal breaker portion, the gasket portion being adapted to engage with the mating surface on at

least one internal wall portion surface of the refrigeration cabinet such that the gasket portion is positioned between the first and second thermal breaker portions to form a substantially air-tight seal.

25. (New)

A modular refrigeration unit for use in a refrigeration cabinet, the refrigeration cabinet including a condenser chamber having at least one insulated wall portion with at least one mating surface thereon and an insulated main chamber, said at least one mating surface defining an opening between the condenser chamber and the main chamber, the modular refrigeration unit comprising:

a condenser assembly;

an evaporator assembly;

a bulkhead assembly positioned between the condenser assembly and the evaporator assembly, the bulkhead assembly having a periphery engageable in said opening between the condenser chamber and the main chamber;

a gasket assembly coupled to one of said bulkhead periphery and said at least one mating surface; and

the modular refrigeration unit being adapted for movement substantially transverse to the bulkhead assembly for engaging the gasket assembly with the other of said bulkhead periphery and said at least one mating surface to form a substantially air-tight seal between the condenser chamber and the main chamber.

26. (New)

A modular refrigeration unit according to claim 25 in which the gasket assembly includes a bulkhead thermal breaker portion mounted onto the bulkhead periphery and a plurality of flexible vanes extending outwardly from the bulkhead thermal breaker portion, the modular refrigeration unit being adapted for movement into the opening in a direction substantially transverse to the bulkhead body portion

for engaging the vanes with said at least one mating surface to form a substantially air-tight seal between the condenser chamber and the main chamber.

27. (New)

A refrigerator comprising:

- a refrigeration cabinet comprising insulated outer walls and at least one access door for accessing an insulated main chamber of the cabinet;

- the refrigeration cabinet comprising a condenser chamber extending inwardly from an aperture in an outer wall of the cabinet, the condenser chamber being at least partially defined by at least one insulated interior wall portion with at least one mating surface thereon, said at least one mating surface being positioned distal to the aperture, said at least one mating surface defining an opening between the condenser chamber and the main chamber;

- a modular refrigeration unit installed in the cabinet, the modular refrigeration unit comprising:

 - a condenser assembly;

 - an evaporator assembly;

 - a bulkhead assembly positioned between the condenser assembly and the evaporator assembly, the bulkhead assembly having a periphery engageable in said opening between the condenser chamber and the main chamber;

 - a gasket assembly coupled to one of said bulkhead periphery and said at least one mating surface; and

- the modular refrigeration unit being adapted for movement substantially transverse to the bulkhead assembly for engaging the gasket assembly with the other of said bulkhead periphery and said at least one mating surface to form a substantially air-tight seal between the condenser chamber and the main chamber.

28. (New)

A refrigerator according to claim 27 in which the gasket assembly includes a bulkhead thermal breaker portion mounted onto the bulkhead periphery and a plurality of flexible vanes extending outwardly from the bulkhead thermal breaker portion, the modular refrigeration unit being adapted for movement into the opening in a direction substantially transverse to the bulkhead body portion for engaging the vanes with said at least one mating surface to form a substantially air-tight seal between the condenser chamber and the main chamber.

29. (New)

A refrigerator according to claim 27 additionally comprising:

- an evaporator shield assembly positioned in the main chamber for channelling a circulatory air flow in the main chamber through an evaporator in the evaporator assembly;

- a plenum positioned adjacent to the evaporator, for guiding the circulatory air flow along a predetermined circulatory air flow path; and

- a partition positioned substantially vertically in the main chamber for directing at least a portion of the circulatory air flow toward the evaporator.

30. (New)

A refrigerator according to claim 20 additionally comprising a third set of louvers positioned in a front panel assembly, the third set being adapted to guide a flow of ambient air in a predetermined direction into the condenser chamber, such that immediate recirculation of air exiting the condenser chamber from the exhaust louvers is substantially prevented.